



WORLD SAILING OFFSHORE SPECIAL REGULATIONS INSPECTION CARD

For inshore races (OSR Appendix B)

Inshore races: Short races, close to shore in relatively warm and protected waters where adequate shelter and/or effective rescue is available all along the course, held in daylight only (OSR 2.01.6)

The present inspection card is based on World Sailing Offshore Special Regulations (OSR) 2026-2027 Appendix B

Yacht: _____ Sail No: _____ Date: ____/____/____
Person in charge/Owner/Skipper/Representative: _____ Signed: _____
Person in charge substitute (OSR 1.02.1): _____
Inspector: _____ Signed: _____
Comments: _____ Number of crew members: _____

The full compliance with World Sailing Offshore Special Regulations (OSR, <http://www.sailing.org>) is the sole responsibility of the person in charge and it cannot be limited to the present inspection card (OSR 1.02).

The OSR do not replace, but rather supplement, the requirements of governmental authority, or any other rules or regulations (OSR 1.01.2).

All equipment required by OSR shall function properly and, if it has expiry date, it will not exceed the expiry date while racing (OSR 2.04.1).

Show the following:	OSR §	Comment
All openings are capable of being immediately secured. Centerboard, daggerboard trunks and the like do not open into the interior of a hull (except via a watertight maintenance hatch with the opening entirely above the Waterline).	3.02.1	
One compass (hand-held is acceptable).	3.24	
One fire extinguisher required if electrical system, engine or stove on board.	4.05	
Lifejacket of appropriate size range for each crewmember, gas inflatable, complies w/ ISO 12402-3 Level 150, manufactured after 2011. Fitted with manual or automatic gas inflation system, crotch/thigh straps, reflective material, whistle and lifting loop (all complying w/ISO 12402-3 or 12402-8). Indelibly marked boat's or wearer's name.	5.01.1 4.17	
Knife strong, securely restrained, readily accessible from deck or cockpit.	4.25	
Anchor (one).	4.06	
One strong bucket with a lanyard and of at least 9 liters capacity.	3.23	
Lifebuoy with drogue.	4.22.3	
Heaving line 15-25m long, diameter ≥ 6mm, readily accessible to cockpit.	4.22.4	